

Model: CYF



Output Pulse		100P/R	25P/R
Output Model		Voltage	Line Driver
Supply Voltage		DC5V-15V/10-30V	DC5V-0.25V
Current Requirement		≤60mA	≤150mA
Signal Level	High	≥Vcc-1V	≥2.5V
	Low	≤0.5V	≤0.5V
Rise/Fall time		≤1us	≤0.1us
Output Phase		A,B,-A,-B	
Frequency Response		≤50kHz	
Isolation resistance		≥20MΩ	
Normal rotational speed		≤200r/min	
Slew speed		600r/min	
Operating temperature		-10~+60°C	
Storage Temperature		-20~+70°C	
Dimension		130mm×70mm×33.5mm	
Switch for resolution		×1,×10,×100	
Switch for Axes		O/X/Y/Z/2/3/4/6	

Specifications

1.External DIA:70*33mm	Slew speed	600r/min
2.Output Model:Voltage /Open Collector/Open Collector/Line Driver	Operating temperature	-10~+60°C
3.Pulse No:25,100	Storage Temperature	-20~+70°C
4.Anti-oil sealing	Dimension	130mm×70mm×33.5mm
	Switch for resolution	×1,×10,×100
	Switch for Axes	O/X/Y/Z/2/3/4/6

